



OASIS TOUCH TECHNOLOGIES

Size	Part No.	Glass	Dimension	Active Area
		L*W(mm)	L*W(mm)	L*W(mm)
10.4"	OTT104P-4F-AL	246x195	256x203	212x159
12.1"	OTT121P-4F-AL	281x220	291x228	247x184
15.1"	OTT151P-4F-AL	340x265	350x273	306x229
15.6"	OTT156P-4K-AL	379x230	389x238	345x194
17"	OTT170P-4F-AL	374x308	384x316	340x272
18.5"	OTT185P-4K-AL	444x267	454x275	410x231
19"	OTT190P-4F-AL	411x337	421x345	377x301
19"	OTT190P-4K-AL	444x293	454x301	410x257
21.5"	OTT215P-4K-AL	511x304	521x312	477x268
22"	OTT220P-4K-AL	508x332	518x340	474x296
23"	OTT230P-4K-AL	544x323	554x331	510x287
23.6"	OTT236P-4K-AL	556x330	566x338	522x294

Technology	Surface Acoustic Wave(SAW)
Sizes	10.4" to 26"(extending)
Resolution	4096 x 4096 ,Z-axis 256
Material	Pure glass(Vandal-proof ,Anti-glare can optional)+Aluminum frame
Waterproof standard	Seal frame to meet IP64 standards
Accuracy	<2mm
Light Transmission	>92% /ASTM
Touch Force	30g
Durability	Scratch-free; More than 50,000,000 touches in one location without failure.
Surface Hardness	Mohs' 7
Multi-touch	Optional , software support
Operating Temp.	-10°C to +60°C
Storage Temp.	-20°C to +70°C
Humidity	10%-90% RH /40°C,
Altitude	3800m
Parts	Connect cable,Double-sided adhesive, dustproof strip
Certificates	CE, FCC, RoHS

Phone : 08600888766

Email : sales@oasistouch.co.in, www.oasistouch.co.in